# **General Purpose Lubricants**

#### WD-40 Lubricant

- Frees rusted and sticky parts
- Gets under water, dries it off and keeps it off
- Non-conductor
- Dry out electrical and electronic parts
- Lubricates squeaks in hard-to-get-at mechanisms
- Silicone-free; no messy residue
- · Lubricates and invisibly shields against moisture and corrosive elements
- Removes tar, grease and adhesives



\$25.40 / Ea Gallon 16 oz Spray \$7.45 / Ea 11 oz Spray \$6.90 / Ea \$5.45 / Ea 8 oz Spray Spray applicator \$3.75 / Ea

# **CRC** Lubricant

- All purpose lubricant offers superior penetrating power that breaks through rust and corrosion while removing scale and dirt
- Stops squeaks and frees rusted parts
- Protects metals from rust and corrosion
- Contains no chlorinated solvents •

Gallon

- ٠ Biodegradable
- **Displaces** water



\$34.65 / Ea \$4.75 / Ea 9 oz Spray \$5.70 / Ea Applicator

# Super Oil

 Solderseal #L10-04 lubricates and protects all metal parts against wear, rust, corrosion, tarnish · Loosens bolts, nuts and



other rusted parts 4 oz can w/spout and twist cap \$2.40 / Ea

# #L212 Liquid Wrench Super Lubricant

- Lubricates
- Protects surface from wear
- Inhibits rust and corrosion
- **Displaces** moisture
- 11 oz. spray

\$3.85 / Ea

# Liquid Wrench Penetrating Oil

- A powerful blend of quick-acting, fastpenetrating solvents that loosens rusted nuts, bolts and parts in seconds
- Frees parts frozen by rust, corrosion, scale, paint, varnish, carbon or gum
- Guaranteed safe on all metals



# #M9-14 Silicone Lubricant Spray

- Environmentally resonsible formula contains no ozone depleters or chlorinated solvents
  - Stops squeaking and sticking, prevents rust and corrosion. lubricates doors, windows, locks, and drawers
- Useful in many other home, shop, industrial, marine, sport and automotive applications

\$3.75 / Ea

 $\sim$ 

NLICON

SPRAY

# #L5-08 Teflon Lube Spray

- Tiny Teflon particles acting as "ball bearings" significantly reduce friction and wear
- Forms a barrier to repel dust, dirt, sand, salt, ice and other abrasive materials
- 8 oz. Net Wt.

#### #L7-16 Chain and Open Gear Lubricant Spray

- · Contains molybdenum disulfide
- Withstands high temperatures and adheres to surfaces under hiah RPM's
- Sprays on and penetrates like an oil, sets up like a grease

\$4.25 / Ea

# **Automotive Oils & Greases**

# Wolf's Head Super Duty Motor Oil

- · For gasoline engines, light duty diesel engines Formulated with oil soluble friction modifiers that reduce internal friction in enaines
- All quarts are packaged 12 per case

SAE 10W-40	\$46.20 / Case
(SG/CD)	\$4.20 / Qt
SAE 10W-30	\$42.35 / Case
(SG/CD)	\$3.85 / Qt
SAE 5W-30	\$42.90 / Case
(SG/CC)	\$3.90 / Qt
SAE 5W-20	\$42.90 / Case
(SG/CC)	\$3.90 / Qt
SAE 20W-50	\$50.60 / Case
(SG/CD)	\$4.60 / Qt

# Wolf's Head Heavy-Duty Motor Oil

· Protects against deposit build-up under low temperature stop-and-go conditions and minimizes varnish build-up



Exceeds many car manufacturers' warranty requirements

SAE 30W (SG/CD)

\$46.75 / Case \$4.25 / Qt

# Kendall Non-Detergent Motor Oil

- Superior, high quality non-detergent oil for API Service SB
- · Fortified to resist oxidation, wear and foaming
  - Recommended for all applications requiring non-detergent type oil

67.10 / Qt
67.10 / Qt
57.10 / Qt



# Kendall Diesel Motor Oil

- For heavy duty diesel
- and gasoline engines All grades meet API

Cummins NTC-400

service CE Approved under



and Mack EO-K/2 Meets requirements MIL-L-46152D and MIL-L-2104E

Super D III

SAE 15W-40 (CE/CD-II/SG) \$26.10 / Gal \$6.40 / Qt

Super D III	
SAE 30 (CE/CD-III/SG)	\$23.75
	<b>*</b>



# Wolf's Head Dexron/MerconIII Automatic **Transmission Fluid**

 Multipurpose power transmission fluid recommended for passenger car and truck automatic transmissions which use Dexron II and Mercon fluids



- Meets requirements of Ford M2C-138CJ and M2C-166H (Type H)
- · Dyed red

\$46.75 / Case \$4.25 / Qt

# Kendall Type F Automatic

- **Transmission Fluid** For use in Ford cars
- and trucks · Nonfriction modified automatic transmission fluid approved for Ford transmissions



Compatible with other fluids meeting Ford spec M2C-33F Dyed red

\$60.50 / Case \$5.50 / Qt

# Universal Gear Lube SAE 85W-140 GL-5

- Recommended for differentials and manual transmissions in passenger cars, trucks, vans, buses, and off-road equipment
- Recommended for equipment operating over a broad temperature range under a variety of load conditions
- High Viscosity Index (VI)
- Exceptionally low pour point
- · Meets and exceeds the requirements for API GL-5, MIL-L-2105D

16 Gal (120 lb)	\$384.00 / Ea
5 Gal (35 lb)	\$117.85 / Ea
Gal	\$40.35 / Ea
Qt	\$11.45 / Ea

#### **NS-MP Hypoid Gear Oil** SAE 80W-90 GL-5

- · Multi-purpose EP gear oil recommended for hypoid, spiral bevel and worm gear axles and limited-slip differentials
- Recommended for manual transmissions which require an extreme pressure GL-5 gear oil
- Meets requirements of MIL-L-2105D

16 Gal (120 lb)	\$384.00 / Ea
5 gal (35 lb)	\$117.85 / Ea
Gal	\$38.85 / Ea
Qt	\$10.95 / Ea

# Kendall GT-1 2 Cycle Lubricant

- · Designed specifically for high performance air cooled and water cooled 2-cycle engines
- An ashless, high dispersant lubricant fortified to minimize scuffing and scoring
- Prediluted to facilitate mixing with gasoline at low temperatures
- NMMA/BIA certified for service TC-W3tm and TC-WIItm at the manufacturers' recommended mixing ratio
- Recommended for snowmobiles, motorcycles and outboards, both premix and oil injected, operated under severe conditions

\$8.20 / Qt \$4.40 / Pt

(GIT)

# Conoco Super-Sta #2 Chassis Grease

- Multi-purpose grease compounded with lithium tackiness agent and extreme pressure additives
- Recommended for automotive, bus and truck equipment; also farm,
- construction and industrial equipment Slowly "bleeds" oil to ensure complete lubrication
- NLGI #2 consistency

16 Gal (120 lb)	\$508.80 / Ea
5 Gal (35 lb)	\$191.10 / Ea
14 oz Cartridge	\$5.40 / Ea

## #L-427 EP Lithium Super Blu-Grease

- An NLGI #2 lithium complex EP grease with excellent lubricating characteristics
- Formulated from a multi-viscosity base oil for operation from -40°F to at least 350°F in continuous service
- Also formulated with a tackiness additive for truck 5th wheel application with excellent rust and corrosion protection
- Recommended for use in heavy duty lubrication, all wheel bearings, universal joints, general ball and roller bearings & throw-out bearings
- Can also be used as distributor cam grease and centralized lube systems



\$7.35 / Ea 14 oz Cartridge \$7.25 / Ea

#### White Lithium Grease

- · Finest quality lithium grease for multipurpose applications
- Long lasting, all weather, waterresistant, high film strength lubricant
- Melt point +360°F., pour point +10°F
- NLGI #2 consistency grease
- Excellent for shop maintenance and field maintenance whenever a multipurpose all weather lubricant is required
- Ideal for gears, latches, cables, bearings, rollers, assembly of parts, chains on fork lift trucks, and tracks



)	\$5.85 / Ea
Ctg.	\$5.65 / Ea
be	\$4.30 / Ea
	\$4.50 / Ea





122

# **Specialty Oils**

# **Machine Oil**

- Solvent-refined, highquality rust and oxidation inhibited oil for air compressors, gear boxes, hydraulic systems, electric motors, and centrifugal, turbine, and deep well pumps
- Machine Oil
- Formulated to have excellent oxidation stability, antirust and antifoam characteristics
- Good antiwear properties

30 WtHeavy Machine Oil	\$23.70 / Gal
Dectol R&O 10	\$9.95 / Qt

20 WtMedium Machine C	iil \$23.70 / Gal
Dectol R&O 68	\$9.95 / Qt
10 WtLight Machine Oil	\$23.70 / Gal
Dectol R&O 46	\$9.95 / Qt

# Hydraulic Oil

• Formulated for use in high-pressure, highoutput systems as well as machine tools, hydraulic jacks, and robotics having stringent filterability requirements

Carries Cincinnati Milacron approvals P-68 service

Meets Vickers. Denison HF-0 and FMC requirements for consumer use \$20.40 / Gal

#### **Quenching Oil**

- Low-viscosity inhibited oils used in steel part quenching for metal tempering
- Quench time for quench oil 22, 17-19 seconds



\$19.40 / Gal

HD Way Lubricant

68

# Way Lube-68

- Extreme pressure lubricant with oiliness additives to prevent stick slip on machine tool ways
- Contains tackiness additives to impede runoff
- Approved by Cincinnati Milacron under spec. P-47 \$25.60 / Gal

## Spindle Oil

- Germ processed, light bodied, highly stable oil from solvent refined base stocks that have been thoroughly dewaxed to give good fluidity at low
- Spindle Oil
- temperatures Designed primarily for textile applications, but is used extensively in other industrial applications and is popular as a top cylinder and valve
- lubricant on high speed natural gas and LP-gas engines \$34.50 / Gal

# Air Tool Oil

- Absorbs moisture to prever rust and corrosion
- Regular use prolongs tool life and improves performance
- Lubricate the internal parts of air driven tools



\$6.75 / Qt

# Lock Ease Graphited Lock Fluid

- Seals out moisture, protects against lock freeeze-ups
- Prevents sticking and corrosion
- Leaves a long-wearing protective graphited film on locks and other mechanisms



# Extra-fine dry lubrication for all parts

\$1.90 / Ea

Clear

# **Cutting Oils**

# **Clear Cutting Oil**

- Nonstaining cutting oil for moderate metal cutting operation where viewing work piece during Cutting Oil machining is desirable Suitable for machining
- brass, copper, aluminum and light machining of iron and mild steel \$34.50 / Gal \$6.75 / Qt



All-purpose premium

oil for use on both

metals

compounded EP cutting

ferrous and nonferrous

- staining may occur on copper or copper-based alloys
- Excellent for cutting ferrous metals over a wide range of machining severity

\$29.50 / Gal \$10.50 / Qt

DARK

CUTTING

OIL

# Water Soluble Cutting Oil

- Blend of mineral oils and emulsifying agents
- Suitable for wide variety of cutting and grinding operations



- A program to prevent growth of odor-causing bacteria should be carefully followed
- Mixes with water as high as 100-to-1 ratio
- Always add the oil to water, never add the water into the oil

\$39.95 / Gal \$11.20/Qt

# **Tap Magic EP-Xtra Cutting Fluid**

- Made for cutting of all metals
- Apply it at the moment your tool comes in contact with the work
- Use it for all machining operations
- You'll get a precise, ultrafine
- microfinish on every metal and alloy Evaporates to cool metal work and tool
- Ozone friendly formula









# Sulphur Base Dark Cutting Oil

# Lubrimatic

## **General Purpose Grease Gun**

- Ideal for household and doit-yourself automotive uses
- Delivers 1 oz. of grease/40
   strokes
- Develops up to 6,000 psi
- Uses standard 14 oz. cartridges



#### #30-200

# \$13.40 / Ea

# Industrial Grease Gun

- Variable/short stroke for easy use in confined areas
- Rugged fully zinc-plated finish
- Dual port head cap with bulk loader fitting for 3-way loading (14 oz cartridge, bulk or suction) and air bleeder valve
- Includes 5-3/8" pipe and coupler
- Develops up to 10,000 psi

#### #30-465

# \$23.35 / Ea

# The Ultimate Grease Gun

- Equipped with 10" grease pipe, HD coupler, longer lever, barrel and lever comfort grips, air bleeder valve, bulk loader fitting, variable stroke and 3-way loading (14 oz cartridge, bulk or suction
- Develops up to 10,000 psi
- Built to take extreme punishment

#### #30-480

# \$42.70 / Ea

# Grease Fittings Assortment

 Includes eight 1/4"-28 fittings: four straight, two 45° and two 90°

#### #11-955



# Midget Grease Gun Kit

- Includes push lock plunger, die cast Thandle that locks in place for loading, 5-1/2" straight grease pipe standard-duty coupler and 3-oz cartridge of multi-purpose #2 lithium grease
- Small, versatile gun allows for front or top pipe placement
- Develops up to 4,500 psi

#30-192

\$18.40 / Kit

# Multi-Purpose Lithium Grease

- Recommended for chassis, universal joints and other general-purpose applications around the home,
- farm or shopWorks best for lubricating rolling parts



\$3.15 / Ea

#11300, 4-pack of 3-oz refills \$9.95/Pkg

# Flexible Grease Hoses

- Rubber with wire braids
- SAE 100 R17 at 3,000 psi working pressure, 12,000-lb. burst
- 1/8" pipe thread on both ends



# Replacement Coupler Tip

- Fits all 1/8" NPT threads
- Recommended working pressure is 3,000 psi
- For hand operated lube equipment only

#05-031

# Pistol Grip Oilers Drawn steel bodies Rugged epoxy finish

- Rugged epoxy finish resists rust
  Rigid spouts have .15" diameter ledge-cone machined tips to lift oil filler dust caps and are non-detachable
- All flex spouts are zinc plated and detachable with a base thread of 1/4"-28



\$8.35 / Ea

#50-509 6 oz. rigid spout pistol oiler

# Funnels

# Super Funnel

- All-purpose utility funnel
- Extra long neck to reach out of the way spots
  2 quart capacity, 18" overall
- 2 quart capacity, 18" overall length, 5" diameter, 1/2"OD tip

#3625



# **Utility Funnel with Screen**

- All-purpose fluid dispenser
- Galvanized steelIncludes screen and 12"
- Includes screen and 12" flexible extension with tapered tip
- 1 quart capacity, 5-3/4" funnel diameter, 17-1/2" overall length

#75-007

\$8.35 / Ea

# Multi-Purpose Plastic Funnels #3508, 1/2 Pint, 4" \$1.45 / Ea #3516, Pint, 6" \$1.60 / Ea #3564, 2-Quart, 8" \$2.45 / Ea

Flexible 0 • Rubber